




Part Number: GHT2314  
 Surface Mount Magnetic Switches - Normally Open Contacts  
 Product Data Sheet

PRODUCT	DIMENSIONS
---------	------------



Drawings not to scale. All dimensions in mm (inches).

SPECIFICATION		
---------------	--	--

CONTACT FORM		Form A (Normally Open)
CONTACT MATERIAL		Rhodium
SWITCHING CAPACITY	Max.	10 W/VA
SWITCHING VOLTAGE	Max.	200 VDC
SWITCHING CURRENT	Max.	0.5A
CARRYING CURRENT	Max.	0.1A
DIELECTRIC STRENGTH	Min.	150VDC
CONTACT RESISTANCE	Max.	150mΩ
INSULATION RESISTANCE	Min.	10 <sup>9</sup> Ω
SWITCHING TIME WITHOUT BOUNCE	Max.	1.4ms
BOUNCE TIME	Max.	1.0ms
RELEASE TIME	Max.	0.3ms
RESONANT FREQUENCY	Typ.	3900Hz
OPERATING FREQUENCY	Max.	500Hz
OPERATION TIME	Max.	1.0ms
VIBRATION	10-1000	20Hz
SHOCK		30G
CAPACITANCE	Typ.	0.5 pF
OPERATING TEMP. RANGE	Deg.	-40 +125 °C
SENSOR BODY MATERIAL		ABS



### NOTE

- Mini Stick-on Surface Mount Contact Switch with side leads
- Flange for Convenient Mounting
- 18" Long Side Wire Leads
- For specific applications, products can be developed on request.

**Made in India**

### ORDERING INFO

**PART NUMBER GHT2314 15 45**

- Type 
- Minimum (AT) Sensitivity 
- Maximum (AT) Sensitivity 